

Keilton + autani

CS107D Series

Line Voltage Dual-Tech Ceiling Sensor



CS107D.A0

Description

The CS107D is a line-voltage dual-tech occupancy sensor that combines PIR and ultrasonic technologies to provide high accuracy and wide coverage. The integrated photocell provides an adjustable ambient light "Hold-OFF" feature. If ambient light exceeds a programmed threshold, the sensor will keep lights off, even when occupancy is detected. Commissioning via the Keilton+autani app allows the sensor to turn a load on and hold it on if either or both technologies detect movement. The CS107D works seamlessly together with other wireless devices in the Keilton+autani system.

Features

- PIR and Ultrasonic technologies
- Integrated Bluetooth
- Ambient light "Hold-OFF" feature

Specifications


Input Voltage	AC120-277V
Frequency	50/60Hz
Resistive	800W Max @ 120VAC
Tungsten	800W Max @ 120VAC
Electronic Ballast	800VA Max @ 120VAC 1600VA Max @ 277VAC
Motor	1/4 HP @ 120VAC
Bluetooth Transmit	100ft Max
Radio Frequency	2.4GHz ± 75MHz
Bluetooth Version	5.0
Housing Material	UL 94-5VA
Indoor/Outdoor Use	Indoor Use Only
Operating Temperature	0°C to 55°C, 32°F to 131°F
Storage Temperature	-30°C to 85°C, -22°F to 185°F
IP Rating	IP20
Color	White
Warranty	5 year warranty
Compliance	UL773A, UL8750, RoHS
Safety	cULus Listed E504054 FCC ID: 2A26YCS107D DID: D061367 DLC: NLTRC5KL0TN

Ordering Information

Model	Description
CS107D.A0	Line Voltage Dual-Tech Ceiling Sensor

Wiring


CS107D




Dimensions

Unit:inch/mm


CS107D



Detection Area



Product Label



The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by LiteTrace is under license. Other trademarks and trade names are those of their respective owners.

App Download



Due to our continued efforts to improve our products, specifications are subject to change without notice.

Contact Us

7090 Columbia Gateway Drive, Suite 140, Columbia, MD 21046, USA

T: +1 443-320-2233 (M-F 9am-5pm ET)

E: support@autani.com